

PC5-T



Features

- ♦ Suitable for complex lighting scenarios
- ♦ The accuracy rate is 98% for normal indoor scene
- ◆ Angel of view up to 140°Horizontal × 120°Vertical
- ♦ Built-in storage (EMMC) Support Offline Storage, Support ANR(Data Automatic Network Replenishment)
- ◆ Support POE Power supply, Flexible Deployment
- ♦ Support static IP and DHCP
- ♦ Applicable to various commercial complexes, supermarkets, stores and other places
- ◆ Privacy-secure Algorithm and Design

Parameters

PC5-T		
General Parameters		
1/4"CMOS Senor		
1280*800@25fps		
1 ~ 25fps		
140°Horizontal × 120°Vertical		
Functions		
Mounting / Suspending		
1.9m~3.5m		
1.1m~9.89m		
Support		
0.5cm~1.2m		
Built-in video analysis intelligent algorithm, support real-time statistics of the number of		
passengers in and out of the area, can exclude the background, light, shadow, shopping		
cart and other stuff.		
≥98%		

Product features and technical specifications are subject to change without further notice 2022 EATACSENS \circledcirc All rights reserved

EA ELECTRONICS CO.,LTD / E-mail: sales@eatacsensor.com / Web: www.eatacsensor.com.



- ·			
Backup	Front end Flash storage, up to 180 days, ANR		
Network Protocols	IPv4、TCP、UDP、DHCP、RTP、RTSP、DNS、DDNS、NTP、FTPP、		
	НТТР		
Ports			
Ethernet	1×RJ45, 1000Base-TX, RS-485		
Power port	1×DC 5.5 x 2.1mm		
Environmental			
Operating	0°C ~ 45°C		
Temperature			
Operating	20% ~ 80%		
Humidity			
Power	DC12V±10%, POE 802.3af		
Power	≤ 4 W		
Consumption			
Mechanical			
Weight	0.46Kg		
Dimensions	143mm x 70mm x 40mm		
Installation	Ceiling Mount / Suspension		

Installation Height and Coverage Width

Installation height	Width of cover
1.9m	1.1m
2m	1.65m
2.5m	4.5m
3.0m	7.14m
3.5m	9.89m

Installation Height and Coverage Area(m²) (Heatmap Function)

Installation height	Width of cover
2.5m	12.19 m²
3.0m	32.13 m²
3.5m	61.71 m²



Dimension

